

Our Docket No.: 51876P381
Express Mail No.: EV339905748US

UTILITY APPLICATION FOR UNITED STATES PATENT
FOR
MICROSTRIP PATCH ANTENNA AND ARRAY ANTENNA USING SUPERSTRATE

Inventor(s):
Won Kyu Choi
Cheol Sig Pyo
Jong Moon Lee
Young Keun Yoon
Yong Heui Cho
Jong-Suk Chae
Jae Ick Choi

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP
12400 Wilshire Boulevard, Seventh Floor
Los Angeles, California 90025
Telephone: (310) 207-3800

MICROSTRIP PATCH ANTENNA AND ARRAY ANTENNA USING SUPERSTRATE

Field of the Invention

5 The present invention relates to a microstrip patch antenna and array antenna using a dielectric superstrate, and particularly to a microstrip patch antenna using a dielectric superstrate and an array antenna using the same, for a wireless communication base station, a wireless local area
10 network, satellite communications and satellite broadcasting.

Description of the Prior Art

 The concept of microstrip radiators was first proposed by
15 Deschamps as early as 1953. There are many advantages and disadvantages of microstrip antennas compared with other microwave antennas. The advantages include lightweight, low volume, low profile planar configurations and low fabrication cost. However, the microstrip antennas have disadvantages
20 such as narrow bandwidth and low antenna gain.

 Figs. 1A and 1B are a cross-sectional view and a perspective view of a typical microstrip patch antenna.

 As shown in Figs. 1A and 1B, a typical microstrip patch antenna has a ground plane 101, a dielectric layer 102, a
25 radiating patch 103, and a feedline 104.

 The dielectric layer 102 is placed on the ground plane 101 that is a conductor and the feedline 104 and the radiating

patch 103 are formed on the dielectric layer 102.

However, a structure of the typical microstrip patch antenna does not provide broadband impedance characteristics.

In order to obtain a high gain antenna required for a
5 base station of a wireless communication system, a wireless
local area network and a satellite, the number of radiating
patches are increased and the size of the antenna is enlarged.

Despite of increase in the number of radiating patches,
it is difficult to obtain a high gain microstrip antenna
10 because of large feeding loss.

To solve the problem of large feeding loss, a microstrip
patch antenna using a superstrate is disclosed by X. H. Shen
in "Effect of superstrate on radiated field of probe fed
microstrip patch antenna", IEEE proc. Micro. Antenna Propag.,
15 Vol. 148, No. 3, pp. 131-146, 2001. 06.

Figs. 2A and 2B are a cross-sectional view and a
perspective view of a microstrip patch antenna using
superstrate disclosed by X. H. Shen.

Referring to Figs. 2A and 2B, a microstrip patch is fed
20 by a coaxial cable. As a dielectric layer having high
permittivity is formed on the microstrip patch, radiating
field is focused on boresight direction.

However, the microstrip antenna of Figs. 2A and 2B has a
problem such as a narrow impedance bandwidth because a
25 radiating patch is on a single layer substrate and it is not
adequate to make an array antenna by using the microstrip
antenna of Figs. 2A because the radiating patch is fed to the

coaxial cable.

For overcoming above mentioned problem, a wideband microstrip patch antenna is disclosed at Korean Patent application No. 2001-47913 entitled "Wideband microstrip patch array antenna with high efficiency."

Figs. 3A and 3B are a cross-sectional view and a perspective view of a conventional microstrip stacked patch antenna printed on dielectric film which is disclosed at Korean Patent application No. 2001-47913.

Referring to Figs. 3A and 3B, a dielectric layer 102 is placed on a ground plane 101, and a feedline 104 and a first radiating patch 103 are formed on the dielectric layer 102.

A foam layer 301 is placed on the feedline 104 and the lower radiating patch 103, a dielectric film 302 is formed on the foam layer 301, and an upper radiating patch 303 is placed on the dielectric film 302.

Although the stacked layers of the microstrip patch antenna is proper to enhance impedance bandwidth characteristics, the antenna gain is not high enough to meet the requirement of the current needs such as a wireless communication base station, a wireless local area network, satellite communications and satellite broadcasting.

Summary of the Invention

Therefore, it is an object of the present invention to provide a microstrip patch antenna using a dielectric

superstrate in order to enhance the antenna gain by stacking radiating patches and dielectric layers.

In accordance with an aspect of the present invention, there is provided a microstrip patch antenna using a dielectric superstrate for having high gain and broadband, including: a lower patch antenna layer having a dielectric layer and a ground plane, for radiating energy by exciting current by a feedline electrically connected to a lower radiating patch on a side of the dielectric layer; an upper patches on a dielectric film electromagnetically coupled by the lower radiating patch; a foam layer for distancing the upper patch antenna layer from the lower patch antenna layer by arranging the foam layer between the lower patch antenna layer and the upper patch antenna layer; and a dielectric superstrate located with predeteremined distance from the upper patch antenna layer.

In accordance with an aspect of the present invention, there is provided a microstrip array antenna, including microstrip patch antennas, each of which uses a dielectric superstrate, wherein the microstrip patch antenna includes: a lower patch antenna layer having a dielectric layer and a ground plane, for radiating energy by exciting current by a feedline electrically connected to a lower radiating patch on a side of the dielectric layer; an upper patches on a dielectric film electromagnetically coupled by the lower radiating patch; a foam layer for distancing the upper patch antenna layer from the lower patch antenna layer by arranging

the foam layer between the lower patch antenna layer and the upper patch antenna layer; and a dielectric superstrate located with predeteremined distance from the upper patch antenna layer,

5 wherein the array antenna is designed using the corporate feeding method and the element spacing of the microstrip patch antennas is more than $1\lambda_0$ at 12GHz to minimize the coupling, wherein although the element spacing in the array is wider than the wavelength in free space, the grating lobes can be
10 reduced by the superstrate.

Brief Description of the Drawings

The above and other objects and features of the instant
15 invention will become apparent from the following description of one embodiment taken in conjunction with the accompanying drawings, in which:

Figs. 1A and 1B are a cross-sectional view and a perspective view of a typical microstrip patch antenna;

20 Figs. 2A and 2B are a cross-sectional view and a perspective view of a conventional microstrip patch antenna using superstrate;

Figs 3A and 3B are a cross-sectional view and a perspective view of a conventional microstrip stacked patch
25 antenna printed on a dielectric film;

Figs. 4A and 4B are a cross-sectional view and a perspective view of a microstrip patch antenna in accordance

with the present invention;

Fig. 5A is a cross-sectional view of a microstrip array antenna using a dielectric superstrate in accordance with the present invention and is an array structure of the microstrip patch antenna of Fig. 4A;

Figs. 5B and 5C are top views of a dielectric layer and a dielectric film in accordance with the present invention;

Fig. 6 is a graph showing gain characteristics and return loss bandwidth characteristics of a microstrip patch antenna having a superstrate shown in Fig. 4 and a microstrip patch antenna without a superstrate shown in Fig. 3; and

Figs. 7, 8A and 8B are graphs showing measured return loss and radiation pattern of a microstrip patch antenna using dielectric superstrate in accordance with the present invention.

Detailed description of the Preferred Embodiments

Hereinafter, one embodiment of the present invention and measurement results will be described in detail with reference to the accompanying drawings.

Figs. 4A and 4B are a cross-sectional view and a perspective view of a microstrip patch antenna in accordance with the present invention.

Referring to Figs. 4A and 4B, a dielectric layer 102 is formed on a ground plane 101, and a feedline 104 and a lower radiating patch 103 are formed on the dielectric layer 102 in

the microstrip patch antenna in accordance with the present invention. The feedline 104 is electrically connected to the lower radiating patch 103.

A foam layer 301 is formed on the feedline 104 and the lower radiating patch 103, a dielectric film 302 is formed on the foam layer 301, and an upper radiating patch 303 is placed on the dielectric film 302.

An airgap 401 having a predetermined thickness is placed on the upper radiating patch 303 and a high permittivity dielectric superstrate 402 having a predetermined thickness is formed over the airgap 401.

The upper radiating patch is stacked upon the lower radiating patch (103) by electromagnetically coupling each other efficiently.

Coupling efficiency is obtained by electromagnetically coupling the upper radiating patch 303 to the lower radiating patch 103 that is connected to the feedline 104.

The bandwidth and the gain of the antenna are determined by the thickness of the dielectric superstrate 402 and a dielectric constant. Also, resonant characteristics can be largely varied by the thickness of the airgap 410.

If the thick dielectric superstrate 402 and high dielectric constant are used, the gain is increased but the bandwidth becomes narrow. If the thin dielectric superstrate 402 and low dielectric constant are used, the gain tends to be decreased but the impedance bandwidth tends to be broadened.

Therefore, it is adequate to use radiating element having

high radiating efficiency and wide bandwidth characteristics along with the superstrate 402 of the present invention for obtaining high gain and wide bandwidth characteristics.

Fig. 5A is cross-sectional view of a microstrip array antenna using dielectric superstrate in accordance with the present invention. The microstrip array antenna of Fig. 5A is array structure of single radiating element. Figs. 5B and 5C are top views of a dielectric layer and a dielectric film in accordance with the present invention.

The microstrip patch antenna is designed so that radiation field radiated from each radiating patch can obtain a high directivity in the dielectric layer 402.

The distance between each radiating patches is more than $1\lambda_0$ in this embodiment.

As shown in Fig. 4A, the thickness of the dielectric layer 402 and the dielectric constant can largely affect the bandwidth and the gain characteristics.

Fig. 6 is a graph showing gain characteristics and return loss bandwidth characteristics of a microstrip patch antenna with a superstrate shown in Fig. 4 and a microstrip patch antenna without a superstrate shown in Fig. 3.

Figs. 7, 8A and 8B are graphs showing measured return loss and radiation pattern of a microstrip patch antenna using dielectric superstrate in accordance with the present invention.

Referring to Fig. 6, the microstrip patch antenna using dielectric superstrate in accordance with the present

invention outperforms the conventional microstrip patch antenna.

The gain of the microstrip patch antenna using dielectric superstrate in accordance with the present invention is enhanced about 4dBi than that of the conventional microstrip patch antenna.

In case of 2×8 microstrip array antenna in accordance with the present invention, 10dB return loss bandwidth is 12.6%, i.e., center frequency is 12GHz, side lobe level in E-plane is less than 10dB, side lobe level in H-plane is less than 15dB, and cross polarization level is less than 25 at boresight.

Also, 2×8 microstrip array antenna in accordance with the present invention has the gain of about 23dBi which is about 3dBi higher than the prior microstrip array antenna.

As mentioned above, the present invention can improve performances of antenna gain, radiation efficiency, and bandwidth characteristics by using radiation element having wide impedance bandwidth and dielectric layer having high permittivity.

Also, a size of the microstrip antenna used in satellite communication systems and satellite broadcasting systems is reduced by using the present invention.

Therefore, the present invention can also be used in the field of wireless local area network because of the high gain characteristics of the present invention.

While the present invention has been shown and described

with respect to the particular embodiments, it will be apparent to those skilled in the art that many changes and modifications may be made without departing from the spirit and scope of the invention as defined in the appended claims.